

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENTS	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	xii
	LIST OF FIGURES	xiii
	LIST OF SYMBOLS	xix
	LIST OF APPENDICES	xx
1	INTRODUCTION	
	1.1 General	1
	1.2 Objective	5
	1.3 Scope of study	5
	1.4 Problem statement	6
2	LITERATURE REVIEW	
	2.1 Flood Mapping	8
	2.2 Flood Hazard Maps	12
	2.3 Flood Hazard Boundary Map	12
	2.4 Calculation of flood depths and velocities	16
	2.4.1 Existing flood maps and topographic data	16

2.4.2	Conveyance calculation	16
2.4.3	One-dimensional hydraulic models with defined flood storage areas	17
2.4.4	Flow routing using a "raster" GIS system	17
2.4.5	Two-dimensional hydraulic modeling using a fixed grid	17
2.4.6	Two-dimensional hydraulic modeling using a triangular mesh	17
2.5	Hydraulic modelling requires in Watershed Studies	17
2.5.1	Flow (for rivers) or sea level (coasts)	17
2.5.2	Flood defences, including location and level	18
2.6	Flood Risk Maps	18
2.7	Software	21
2.7.1	HEC - RAS	24
2.7.1.1	Advantage Of HEC - RAS	25
2.7.1.2	Disadvantage of HEC – RAS	25
2.7.2	Storm model water management SWMM	25
2.7.2.1	History of SWMM	26
2.7.2.2	Model Parameters	27
2.7.2.3	SWMM objects	27
2.7.2.4	Application of SWMM	27
2.7.3	INFOWORKS	28
2.7.3.1	Structure of INFOWORKS model	30
2.7.3.2	Using model in simulation	31
2.7.3.3	limitations	32
2.7.3.4	Data import	32
2.7.3.5	Data export	32
2.7.3.6	Data storage	33
2.7.3.7	Model build functionality	33
2.7.3.8	Geographical model building tools	33

2.7.3.9	Grid and property sheet model data entry and view	34
2.7.3.10	Integrated ground modeling	34
2.7.3.11	Catchment boundaries and Area-take off	34
2.7.3.12	Interactive network simplification through query analysis	35
2.7.3.13	Model validation	35
2.7.3.14	ISIS Flow, Hydrology and PDM Engines	35
2.7.3.15	Clear graphical presentation and Analysis	36
2.7.3.16	Develop the last version in compare previous versions	37

3

METHODOLOGY

3.1	Introduction	39
3.2	Main considerations	39
3.3	Hydrological model development	41
3.4	Data collection	41
3.4.1	River alignment	42
3.4.2	River profile	42
3.4.3	Hydrological data	42
3.4.4	Water level data	44
3.4.5	River cross section	45
3.5	Calibration	45
3.6	Sensitivity analysis of the model	45
3.7	Simulation	46
3.8	The process for hydrodynamic modelling	46
3.8.1	Hydraulic and hydrological data	46

3.8.2	Hydrologic analysis	46
3.8.3	Hydraulic analysis	47
3.8.4	GIS process	47
3.8.5	Software selection	48
3.9	Mathematical background of software	48
3.9.1	Steady flows	49
3.9.2	Theoretical basis	51
	3.9.2.1 Hydrodynamic Channel Flows	51
3.10	Flood map accuracy	53
3.11	Type of flooding	54
3.12	Flood Mapping Model with Infoworks	57
3.13	Study area	60

4

ANALYSIS

4.1	Introduction	65
4.2	Hydrology analysis	65
4.3	Hydraulic analysis	65
4.3.1	Boundary condition	66
	4.3.1.1 Hydrograph for all Subcatchments in 100 ARI	66
	4.3.1.2 Most upstream Chainage (dummy) Characteristics	70
	4.3.1.3 Tidal data	70
4.3.2	Calibration of InfoWorks RS model	72
4.3.3	Water level simulation for high and low flow	75
4.3.4	Simulating the water level in Whole River profile for high and low flow	80
	4.3.4.1 Water level simulation (100-ARI)	81
	4.3.4.2 Water level simulation (50-ARI)	84
	4.3.4.3 Water level simulation (20-ARI)	86
	4.3.4.4 Water level simulation (10-ARI)	88
	4.3.4.5 Water level simulation (5-ARI)	90

	4.3.4.6 Water level simulation (2-ARI)	92
4.4	Flood extent map	94
5	RESULT AND DISCUSSION	98
5.1	Introduction	98
5.2	Model simulation results to produce flood point	98
5.3	Model simulation results to compare the level of water between all ARIs	102
5.4	Compare model simulation results for high and low flow and stage during all ARIs	104
5.5	Model simulation results to compare flood depth in left and right side bank of Sg Skudai in all ARIs	108
5.6	To compare model simulation results between InfoWorks and XP SWMM in all ARIs	111
5.7	Compare model simulation results for high and low flow and velocity during all ARIs	117
5.8	Flood extent map (flood hazard map)	121
6	CONCLUSION AND RECOMENDATION	
6.1	Conclusion	125
6.2	Recommendations	126
	REFRENCES	128
	APPENDIX A	
	APPENDIX B	

LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	Guidance on debris factors for different flood depths, velocities and dominant land uses	15
2.2	Area Vulnerability	15
4.1	Tidal harmonic constituent for Johor Bahru	71
4.2	Calibration statistic report	74
6.1	The location of flood areas effected during various ARIs	124

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
1.1	Hydrologic Cycle	1
1.2	Climatic zones in the tropics	2
1.3	Location of Wilayah Pembangunan Iskandar WPI	4
1.4	Flood Prone Areas WPI	31
2.1	Structure of an InfoWorks Model	13
3.1	Flow chart of the project processes	40
3.2	A constant slope hydrograph separation method of Hewlett and Hibbert	44
3.3	The Location of the Study Area	61
3.4	Topography of Sg. Skudai Catchment	62
3.5	The Location of the Sg Skudai catchment	63
3.6	Catchment Delineation of Sg Skudai	64
4.1	Subcatchment A - 100AR	66
4.2	Subcatchment B - 100ARI	66
4.3	Subcatchment B1 - 100ARI	67
4.4	Subcatchment C - 100ARI	67
4.5	Subcatchment B2 - 100ARI	67
4.6	Subcatchment B3 - 100ARI	67
4.7	Subcatchment E - 100ARI	67
4.8	Subcatchment D - 100ARI	67
4.9	Subcatchment B4 - 100ARI	68
4.10	Subcatchment F - 100ARI	68
4.11	Subcatchment B5 - 100ARI	68
4.12	Subcatchment G - 100ARI	68

4.13	Subcatchment Sg Senai - 100ARI	68
4.14	Subcatchment Skudai - 100ARI	68
4.15	Subcatchment B6 - 100ARI	69
4.16	Subcatchment B7 - 100ARI	69
4.17	Subcatchment J - 100ARI	69
4.18	Subcatchment M - 100ARI	69
4.19	Subcatchment K - 100ARI	69
4.20	Subcatchment L - 100ARI	69
4.21	Subcatchment B8 - 100AR	70
4.22	Subcatchment N - 100ARI	70
4.23	Subcatchment B9 - 100ARI	70
4.24	Subcatchment O - 100ARI	70
	One cycle during in the spring high tide for Sg	
4.25	Skudai	71
	Comparison observed data and simulated result with	
4.26	$n = 0.03, 0.05$	72
	Comparison observed data and simulated result with	
4.27	$n = 0.03$	73
	Comparison observed data and simulated result with	
4.28	different Manning Coefficient	73
4.29	Kampung Laut- 100 ARI	75
4.30	PUB- 100 ARI	76
4.31	Senai Town- 100ARI	76
4.32	Opposite Railway Station-100 ARI	77
4.33	Kampung Pertanian-100 ARI	77
4.34	Taman Indahpura, Kulai-100 ARI	78
4.35	Taman kulai Baru-100 ARI	78
4.36	Sengkang -100 ARI	79
4.37	The first upstream of Sg Skudai ,part A	80
4.38	The second upstream of Sg Skudai, part B	80
4.39	The downstream of Sg Skudai, part C	81

4.40	Water level profile in part A - 100 ARI	82
4.41	Water level profile in part B - 100 ARI	82
4.42	Water level profile in part C - 100 ARI	83
4.43	Water level profile in part A - 50 ARI	84
4.44	Water level profile in part B - 50 ARI	84
4.45	Water level profile in part C - 50 ARI	85
4.46	Water level profile in part A - 20 ARI	86
4.47	Water level profile in part B - 20 ARI	86
4.48	Water level profile in part C - 20 ARI	87
4.49	Water level profile in part A - 10 ARI	88
4.50	Water level profile in part B - 10 ARI	88
4.51	Water level profile in part C - 10 ARI	89
4.52	Water level profile in part A - 5 ARI	90
4.53	Water level profile in part B - 5 ARI	90
4.54	Water level profile in part C - 5 ARI	91
4.55	Water level profile in part A - 2 ARI	92
4.56	Water level profile in part B - 2 ARI	92
4.57	Water level profile in part C - 2 ARI	93
4.58	The flood effect area from Danga Bey to Perling (0 – 6400 m), 100 ARI	94
4.59	The flood effect area from Taman Sutera Utama to Kg Laut (6400 – 11500 m), 100 ARI	95
4.60	The flood effect area from Kg Laut to L/raja U-S (11500 – 16500 m), 100 ARI	95
4.61	The flood effect area from Tmn Sepakat to Kaw Perindustrian Senai (16500 – 22500 m), 100 ARI	96
4.62	The flood effect area from Jin Kg Separa to Tmn Mas (22500 – 30500 m), 100 ARI	96
4.63	The flood effect area Tmn Mewah (30500 - 32000 m), 100 ARI	97
5.1	The water level in 100 ARI from Sengkan until	99

	Danga Bay	
5.2	The water level in 50 ARI from Sengkan until Danga Bay	99
5.3	The water level in 20 ARI from Sengkan until Danga Bay	100
5.4	The water level in 10 ARI from Sengkan until Danga Bay	100
5.5	water level in 5 ARI from Sengkan until Danga Bay	101
5.6	The water level in 2 ARI from Sengkan until Danga Bay	101
5.7	The water level in 5 ARI from Sengkan until Danga Bay	103
5.8	The simulation results for high and low flow, Danga Bay - o m	104
5.9	The simulation results for high and low flow, Taman Sepaakat - 17000 m	105
5.10	The simulation results for high and low flow, Kaw Perindustrian Senai - 21000 m	105
5.11	The simulation results for high and low flow, Kulai- 27000 m	106
5.12	The simulation results for high and low flow, Taman Mas- 28500 m	106
5.13	The simulation results for high and low flow, Kg Sengkang- 32000 m	107
5.14	The simulation results for high and low flow, Perling- 5000 m	107
5.15	The simulation results to compare flood depth in left side bank of Sg Skudai	109
5.16	The simulation results to compare flood depth in right side bank of Sg Skudai	110

5.17	To compare model simulation results between InfoWorks and XP SWMM in 100 ARI	112
5.18	To compare model simulation results between InfoWorks and XP SWMM in 50	113
5.19	To compare model simulation results between InfoWorks and XP SWMM in 20 ARI	114
5.20	To compare model simulation results between InfoWorks and XP SWMM in 10 ARI	115
5.21	To compare model simulation results between InfoWorks and XP SWMM in 5 ARI	116
5.22	The simulation results for high and low flow, Danga Bay - 0 m	117
5.23	The simulation results for high and low flow, Taman Sepaakat - 17000 m	118
5.24	The simulation results for high and low flow, Kaw Perindustrian Senai - 21000 m	118
5.25	The simulation results for high and low flow, Kulai- 27000 m	119
5.26	The simulation results for high and low flow, Taman Mas- 28500 m	119
5.27	The simulation results for high and low flow, Kg Sengkang- 32000 m	120
5.28	The simulation results for high and low flow, Perling- 5000 m	120
5.29	Flood extent map simulated with InfoWorks for 100 ARI, Sg Skudai	121
5.30	Flood extent map simulated with InfoWorks for 50 ARI, Sg Skudai	122
5.31	Flood extent map simulated with InfoWorks for 20 ARI, Sg Skudai	122
5.32	Flood extent map simulated with InfoWorks for 2	123

	ARI, Sg Skudai	
5.33	Distribution of Various Flood Prone and Flood Areas in IM, 2007, Sg Skudai (provided by DID)	123

LIST OF SYMBOLS

HR	-	Flood hazard
d	-	Depth of flooding
V	-	Velocity of flood water
DF	-	Debris factor
g	-	Gravity
S_0	-	Slope of river
S_f	-	Loss of friction
q	-	Lateral inflow
K	-	Channel conveyance
R	-	Hydraulic radius
P	-	The length of the wetted perimeter
n	-	Manning's roughness coefficient

LIST OF APPENDIX

APPENDIX	TITLE	PAGE
A	FLOW FOR EVERY SUBCACHMENTS IN SKUDAI RIVER FOR 100 ARI	132
B	SOME PARAMETERS HAS BEEN MODELED BY INFOWORKS RS FOR SKUDAI RIVER - 100 ARI	141